



*Technical Data*

	Bravo II	Bravo III	Bella C
Rim diameter	10" -24"	10" -26"	
Rim width	1.5" - 20"	1" - 20"	
Max. wheel weight	65 Kg		
Balancing accuracy	1 gr		
Rotation Speed	230 RPM	167 RPM	
Cycle time	6 Sec	7 Sec	
Power Supply	220 - 230 v - 50 Hz- 1ph- 600 Watt	220 - 230 v - 50 Hz- 1ph- 700 Watt	
Braking Pedal	No	Yes	
Automatic measurement of wheel diameter and distance	Yes	Yes	
Automatic measurement of wheel width	No	Yes	

39100 Bolzano Maso Della Pieve Str.nr. 4/f ITALY  
 Tel : +39 - 471263755 Direct : +37- 282873136 Fax : +39 - 471267009  
 Sales@boltech.it

# **T3** PIONEER OF TECHNOLOGY **BOLTECH**



## **WHEEL BALANCERS with Color Monitor**

*Wheel Balancer with Micro Processor and Color Monitor for car wheels, motorcycle wheels and van wheels*

**BRAVO II , BRAVO III , BELLA C**



CE  **SELECT YOUR COLOR**



## Specification

- Optimized speed and high precision
- Color LCD Monitor display
- Simple and intuitive GUI
- Special programs for car motorbike and ALU wheels



- Windows CE - Based software
- Haweka quick nut
- Brake pedal
- Wheel protection guard
- Best wheel mounting system

- Special design with curve

Wheel Protection Guard  
( Optional perfer to local recommendations )



Color LCD Monitor display with  
Simple and intuitive GUI  
Accurate Smart Board



Balancing Accessories



Universal Adaptors



HAWEKA Quick Nut  
( only BRAVO III and Bella C )

Follow us by your smart device  
[www.boltech.it](http://www.boltech.it)



Follow us by your smart device  
[www.boltech.it](http://www.boltech.it)

